

Ied jammer ppt , pocket mobile jammer ppt

[Home](#)

>

[gps walkie talkie](#)

>

ied jammer ppt

- [4g 5g jammer](#)
- [4g 5g jammer](#)
- [5g jammer](#)
- [5g jammer](#)
- [5g 4g 3g jammer](#)
- [5g 4g 3g jammer](#)
- [5g 4g jammer](#)
- [5g 4g jammer](#)
- [5g all jammer](#)
- [5g all jammer](#)
- [5g cell jammer](#)
- [5g cell jammer](#)
- [5g cell phone jammer](#)
- [5g cell phone jammer](#)
- [5g cell phone signal jammer](#)
- [5g cell phone signal jammer](#)
- [5g frequency jammer](#)
- [5g frequency jammer](#)
- [5g jammer](#)
- [5g jammer](#)
- [5g jammer uk](#)
- [5g jammer uk](#)
- [5g jammers](#)
- [5g jammers](#)
- [5g mobile jammer](#)
- [5g mobile jammer](#)
- [5g mobile phone jammer](#)
- [5g mobile phone jammer](#)
- [5g phone jammer](#)
- [5g phone jammer](#)
- [5g signal jammer](#)
- [5g signal jammer](#)
- [5g wifi jammer](#)
- [5g wifi jammer](#)
- [5ghz signal jammer](#)
- [5ghz signal jammer](#)

- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [esp8266 wifi jammer 5ghz](#)
- [esp8266 wifi jammer 5ghz](#)
- [fleetmatics australia](#)
- [fleetmatics customer service number](#)
- [fleetmatics now](#)
- [fleetmatics tracker](#)
- [g spy](#)
- [gj6](#)
- [glonass phones](#)
- [gps 1600](#)
- [gps portable mobil](#)
- [gps walkie talkie](#)
- [green and white cigarette pack](#)
- [green box cigarettes](#)
- [green box of cigarettes](#)
- [gsm coverage maps](#)
- [gsm phone antenna](#)
- [gsm stoorzender](#)
- [gsm störare](#)
- [gsm глушилка](#)
- [harry potter magic wand tv remote](#)
- [harry potter wand kymera](#)
- [hawkeye gps tracking](#)
- [how high is 60 meters](#)
- [how to block a telematics box](#)
- [how to disable geotab go7](#)
- [how to erase drivecam](#)
- [i drive cam](#)
- [irobot 790](#)
- [jammer 5g](#)
- [jammer 5g](#)
- [jammer 5ghz](#)
- [jammer 5ghz](#)
- [jammer wifi 5ghz](#)
- [jammer wifi 5ghz](#)
- [l3 l4](#)
- [malbro green](#)
- [marboro green](#)
- [marlboro green price](#)
- [marlboro greens cigarettes](#)
- [marlboro mini pack](#)
- [marlbro green](#)
- [mini antenna](#)
- [mini phone](#)
- [phs meaning](#)

- [portable wifi antenna](#)
- [que significa cdma](#)
- [recorder detector](#)
- [rf 315](#)
- [rfid scrambler](#)
- [skype nsa](#)
- [spectrum mobile review](#)
- [spy webcams](#)
- [three antenna](#)
- [uniden guardian wireless camera](#)
- [uniden wireless security](#)
- [wifi 5g jammer](#)
- [wifi 5g jammer](#)
- [wifi jammer 5ghz](#)
- [wifi jammer 5ghz](#)
- [wifi jammer 5ghz diy](#)
- [wifi jammer 5ghz diy](#)

Permanent Link to Innovation: Improving Dilution of Precision

2021/03/11

A Companion Measure of Systematic Effects By Dennis Milbert GPS receivers must deal with measurements and models that have some degree of error, which gets propagated into the position solution. If the errors are systematically different for the different simultaneous pseudoranges, as is typically the case when trying to correct for ionospheric and tropospheric effects, these errors propagate into the receiver solution in a way that is fundamentally different from the way that random errors propagate. So in addition to dilution of precision, we need a companion measure of systematic effects. In this month's column, we introduce just such a measure. INNOVATION INSIGHTS by Richard Langley WE LIVE IN AN IMPERFECT WORLD. We know this all too well from life's everyday trials and tribulations. But this statement extends to the world of GPS and other global navigation satellite systems, too. A GPS receiver computes its three-dimensional position coordinates and its clock offset from four or more simultaneous pseudoranges. These are measurements of the biased range (hence the term pseudorange) between the receiver's antenna and the antenna of each of the satellites being tracked. The receiver processes these measurements together with a model describing the satellite orbits and clocks and other effects, such as those of the atmosphere, to determine its position. The precision and accuracy of the measured pseudoranges and the fidelity of the model determine, in part, the overall precision and accuracy of the receiver-derived coordinates. If we lived in an ideal world, a receiver could make perfect measurements and model them exactly. Then, we would only need measurements to any four satellites to determine our position perfectly. Unfortunately, the receiver must deal with measurements and models that have some degree of error, which gets propagated into the position solution. Furthermore, the geometrical arrangement of the satellites observed by the receiver — their elevation angles and azimuths — can significantly affect the precision and accuracy of the receiver's solution, typically degrading them. It is common to express the degradation or dilution by dilution of

precision (DOP) factors. Multiplying the measurement and model uncertainty by an appropriate DOP value gives an estimate of the position error. These estimates are reasonable if the measurement and model errors are truly random. However, it turns out that this simple geometrical relationship breaks down if some model errors are systematic. If that systematic error is a constant bias and if it is common to all pseudoranges measured simultaneously, then the receiver can easily estimate it along with its clock offset, leaving the position solution unaffected. But if the errors are systematically different for the different simultaneous pseudoranges, as is typically the case when trying to correct for ionospheric and tropospheric effects, these errors propagate into the receiver solution in a way that is fundamentally different from the way that random errors propagate. This means that in addition to DOP, we need a companion measure of systematic effects. In this month's column, Dennis Milbert introduces just such a measure — the error scale factor or ESF. ESF, combined with DOP, forms a hybrid error model that appears to more realistically portray the real-world GPS precisions and accuracies we actually experience.

"Innovation" features discussions about advances in GPS technology, its applications, and the fundamentals of GPS positioning. The column is coordinated by Richard Langley, Department of Geodesy and Geomatics Engineering, University of New Brunswick. The recent edition of the Standard Positioning Service (SPS) Performance Standard (PS) and the corresponding document for the Precise Positioning Service (PPS) both emphasize a key element. They only specify the GPS signal-in-space (SIS) performance. Since these standards do not define performance for any application of a GPS signal, it becomes even more important to understand the relationship of signal statistics to positioning accuracy. Historically, as well as in Appendix B of the SPS-PS and PPS-PS, this relationship is modeled by covariance elements called dilution of precision (DOP). Many references are available which describe DOP. The core of DOP is the equation of random error propagation: $Q_x = (A^T Q^{-1} A)^{-1}$ where, for n observations, A is the $n \times 4$ matrix of observation equation partial differentials, Q is the $n \times n$ covariance matrix of observations, and Q_x is the 4×4 covariance matrix of position and time parameters (X, Y, Z, T) used to compute DOPs. This equation describes the propagation of random error (noise) in measurements into the noise of the unknown (solved for) parameters. Elements of the Q_x matrix are then used to form the DOP. The equation above is linear for any measurement scale factor of Q . For example, halving the dispersion of the measurements will halve the dispersion of the positional error. This scaling behavior is exploited when forming DOP where, by convention, Q is taken as the identity matrix, I . DOPs then become unitless, and are treated as multipliers that convert range error into various forms of positional error. Thus, we see relationships in the SPS-PS Appendix B such as: $UHNE = UERE \times HDOP$ where $UERE$ is user equivalent range error, $HDOP$ is horizontal dilution of precision, and $UHNE$ is the resulting user horizontal navigation error. DOP is a model relationship between signal statistics and position statistics based on random error propagation. But, since the cessation of Selective Availability (SA), the GPS signal in space now displays less random dispersion than the average systematic effects of ionosphere and troposphere propagation delay error. It's useful to test if a random error model can capture the current behavior of GPS positioning on the ground. The Federal Aviation Administration collects GPS data at the Wide Area Augmentation System (WAAS) reference stations and analyzes GPS SPS performance.

These analyses are documented in a quarterly series called the Performance Analysis (PAN) Reports. To test horizontal and vertical accuracy, the 95th percentile of positional error, taken comprehensively over space and time, without any subsetting whatsoever, is chosen. This measure is always found in Figures 5-1 and 5-2 of the PAN reports. Note that the Appendix A 95% “predictable accuracy” in the reports through PAN report number 51 refers to a worst-site condition and cannot be considered comprehensive. The PAN report 95th percentiles of positional error measured since the cessation of SA are reproduced in FIGURE 1. Figure 1. Accuracy (95th percentile) of horizontal and vertical L1-only point positioning. GPS data are gathered at WAAS reference stations, analyzed quarterly, and published in the PAN reports. The red line is vertical accuracy and the blue line is horizontal accuracy. By the DOP error model, the positional error should be the product of the underlying pseudorange error times HDOP or vertical DOP (VDOP). It is convenient to form the vertical to horizontal positional error ratio, V/H, shown in FIGURE 2. This error ratio should, formally, be independent of the magnitude of the range error. The error ratio should reflect the GPS constellation geometry. One expects the positional error ratio, V/H, to be relatively uniform, and it should also equal the VDOP/HDOP ratio. However, Figure 2 shows a number of spikes (from PAN Reports 37, 40, 44, 64) in the error ratio, and a general increase over the past nine years. The positional error ratios in Figure 2 do not portray the uniform behavior expected for a DOP error model based on random error propagation. Figure 2. Ratio of the vertical/horizontal accuracy (95th percentile). The spikes indicate effects that are not caused by constellation geometry or signal-in-space error. The PAN reports form a challenge to our ability to understand and describe the measured performance of the GPS system. In the past, when SA was imposed on the GPS signal, the measured pseudorange displayed random, albeit time-correlated, statistics. DOP was effective then in relating SA-laden range error to positional error. Now, with SA set to zero, the role of DOP should be revisited. In this article, I will introduce a hybrid error model that takes into account not only the effects of random error but also that of systematic error due to incomplete or inaccurate modeling of observations. But first, let’s examine predicted GPS performance based on DOP calculations alone. Random Error Propagation FIGURE 3 displays detail of a 24-hour HDOP time series. Considerable short wavelength structure is evident. Spikes as thin as 55 seconds duration can be found at higher resolutions. Given the abrupt, second-to-second transitions in DOP, and given that the GPS satellites orbit relative to the Earth at about 4 kilometers per second, one may suspect that short spatial scales as well as short time scales are needed to describe DOP behavior. Figure 3. All-in-view HDOP, July 20, 2007, near the Washington Monument, 5° elevation angle cutoff. Note the abrupt transitions, and that HDOP is around 1.0. VDOP (not pictured) is about 1.5. To investigate DOP transitions, the conterminous United States (CONUS) was selected as a study area. HDOP and VDOP, with a 5° elevation-angle cutoff, were computed using an almanac on a regular 3 minute by 3 minute grid over the region 24°-53° N, 230°-294° E. These DOP grids were computed at 2,880 30-second epochs for July 20, 2007, yielding more than two trillion DOP evaluations. This fine time/space granularity was selected to capture most of the complex DOP structure seen in Figure 3. FIGURE 4 plots the HDOP distribution over CONUS and parts of Canada and Mexico at 02:40:30 GPS Time. This epoch was selected to show an HDOP excursion (HDOP 4 2.58) seen in the

red zone just north of Lake Ontario. DOPs are rather uniform within zones, and these zones have curved boundaries. The boundaries are sharply delineated and move geographically in time, which explains the jumps seen in high-rate DOP time series (as in Figure 3). The broad, curved boundaries seen in Figure 4 are the edges of the footprints of the various GPS satellites. The gradual variation in hue within a zone shows the gradual variation of DOP as the spatial mappings of the local elevation angles change for a given set of GPS satellites in a region. Figure 4. HDOP, July 20, 2007, 02:40:30 GPS Time, 5° cutoff. The curved boundaries, which show abrupt transitions in DOP, are the edges of the footprints of various GPS satellites. The 2,880 color images of HDOP (and VDOP) were converted into an animation that runs 4 minutes and 48 seconds at 10 frames per second. The effect is kaleidoscopic, as the various footprints cycle across one another, and as the zones change color. The footprint boundaries transit across the map in various directions and create a changing set of triangular and quadrilateral zones of fairly uniform DOP. There is no lower limit to temporal or spatial scale of a given DOP zone delimited by three transiting boundaries. The size of a zone can increase or shrink in time. Zones can take a local maximum, a local minimum, or just some intermediate DOP value. And the DOP magnitude in a given zone often changes in time. The animation shows that the DOP maximums are quite infrequent, and the DOPs generally cluster around the low end of the color scale. The animations are available. To get a quantitative measure of distribution, the HDOPs (and VDOPs) are histogrammed with a bin width of 0.01 in FIGURE 5. Tabulations of various percentiles, computed from the bin counts, are displayed in TABLE 1. HDOP ranges from 0.600 to 2.685 and VDOP ranges from 0.806 to 3.810. Figure 5. HDOP, July 20, 2007, 5° cutoff. DOP has a strong central tendency and a tail showing rare instances of large DOP. Here HDOP ranges from 0.600 to 2.685. Chart: GPS World Since the DOP zone boundaries are related to satellites rising and setting, it is natural to expect a relation to a selected cutoff limit of the elevation angle. As a test, DOP was recomputed with a 15° cutoff limit, and histogrammed with a bin width of 0.01 in FIGURE 6. Tabulations of various percentiles, computed from the bin counts, are displayed in TABLE 2. HDOP ranges from 0.735 to 26.335, and VDOP ranges from 1.045 to 72.648. Figure 6. HDOP, July 20, 2007, 15° cutoff. DOP is sensitive to cutoff angle. Here HDOP ranges from 0.735 to 26.335. This is a large increase over the HDOP with a 5° cutoff. The Figures 5 and 6 and Tables 1 and 2 show that DOPs are markedly sensitive to cutoff angles. The histogram tails increase and the maximum DOPs dramatically increase as the cutoff angle is increased. The 95th percentile HDOP increases by about 50 percent when the cutoff angle increases from 5° to 15°. The solutions weaken to some degree and the poorer solutions get much worse. The effect is somewhat greater for VDOP. One normally considers DOP as a property of the satellite constellation that has a space-time mapping. DOP is seen to strongly depend upon horizon visibility. This is a completely local property that is highly variable throughout the region. Clearly, DOP depends on the antenna site as well as the constellation. Systematic Error Propagation It is known that certain error sources in GPS are systematic. Such errors will display different behaviors from random error. For example, the impact of ionosphere and troposphere error on GPS performance has been recognized in the literature (see "Further Reading"). DOP is not successful in modeling systematic effects. A new metric for systematic positional error is needed. Consider a systematic

bias, b , in measured pseudorange, R . One may propagate the bias through the weighted least-squares adjustment: $(A^T Q^{-1} A) x = A^T Q^{-1} y$ by setting the $n \times 1$ vector, $y = b$. Vector x will then contain the differential change (error) in coordinates (δx , δy , δz , δt) induced by the bias. The coordinate error can then be transformed into the north, east, and up local horizon system (δN , δE , δU). Positional systematic error is defined as horizontal error, $(\delta N^2 + \delta E^2)^{1/2}$, and vertical error, $|\delta U|$. As with DOP, the equations above are linear for any measurement bias scale factor, k , which applies to all satellite pseudoranges at an epoch. For example, if one halves a bias that applies to all pseudoranges (for example, $k y$), then one will halve the associated coordinate error, $k x$. Analogous to DOP, we take bias with a base error $b = 1$, to create a unitless measure that can be treated as a multiplier. We now designate the horizontal error as horizontal error scale factor (HESF) and vertical error as vertical error scale factor (VESF). This adds a capability of developing error budgets for systematic effects that parallels DOP. Systematic errors in GPS position solutions have a distinctly different behavior than random errors. This is illustrated by a trivial example. If one repeats any of the tests above with a constant value, c , for the bias, one will find that, aside from computer round-off error, no systematic error propagates into the position. The coordinates are recovered perfectly, and the constant bias is absorbed into the receiver time bias parameter, δt . This is no surprise, since the GPS point position model is constructed to solve for a constant receiver clock bias. The ionosphere and troposphere, on the other hand, cause unequal systematic errors in pseudoranges. These systematic errors are greater for lower elevation angle satellites than for higher elevation angle satellites. So, unlike the trivial example above, these errors cannot be perfectly absorbed into δt . The systematic errors never vanish, even for satellites at zenith. One may expect some nonzero positional error that does not behave randomly. The systematic effect of the ionosphere and troposphere differ through their mapping functions. These are functions of elevation angle, E , and are scale factors to the systematic effect at zenith ($E = 90^\circ$). Because of the different altitudes of the atmospheric layers, the mapping functions take different forms. For this reason, systematic error scale factors (ESFs) for the ionosphere and troposphere must be considered separately. Ionosphere Error Scale Factor. Following Figure 20-4 of the Navstar GPS Space Segment/Navigation User Interfaces document, IS-GPS-200D, the ionospheric mapping function associated with the broadcast navigation message, F , is $F = 1.0 + 16.0 (0.53 - E)^3$ where E is in semicircles and where semicircles are angular units of 180 degrees and of π radians. Since the base error is considered to be $b = 1$ for ESFs, y is simply populated with the various values of F appropriate to the elevation angles, E , of the various satellites visible at a given epoch. The resulting HESF and VESF values will portray how systematic ionosphere error will be magnified into positional error, just as DOPs portray how random pseudorange error is magnified into positional error. As was done with the DOPs, more than two trillion ionosphere HESFs (and VESFs) were computed for CONUS and histogrammed in FIGURE 7. Tabulations of various percentiles, computed from the bin counts, are displayed in TABLE 3. Ionosphere HESF ranges from 0.0 to 0.440 and VESF ranges from 1.507 to 2.765. Figure 7. HESF, ionosphere, July 20, 2007, 5° cutoff. The HESF-I are much smaller than the HDOP. The VESF-I (not depicted) have an average larger magnitude than the VDOP. The distribution of the HESF-I in Figure 7 differs profoundly from HDOP. Ionosphere error is seen to have a weak mapping

into horizontal positional error, with HESF-I values approaching zero, and having a long tail. The VESF-I is roughly comparable to the magnitude of the ionosphere mapping function at a low elevation angle. The VESFs also fall into a fixed range, without long tails, and are skewed to the right. The percentiles in Table 3 show ionosphere error has a greater influence on the height than that predicted by DOP. Systematic Range Error and Height. Both troposphere and ionosphere propagation error leads to error in height. The mechanism underlying the behavior in Table 3 is not obvious. Consider the simplified positioning problem in FIGURE 8, where we solve for two unknowns: the up-component of position and receiver bias, dt (which includes effects common to all pseudoranges measured at the same time, such as the receiver clock offset). The atmosphere will cause the pseudoranges AO, BO, and CO to measure systematically longer. However, the ionosphere error will be about three times larger at low elevation angles than at the zenith. (Troposphere error will be about 10 times larger at low elevation angles than at the zenith.) Figure 8. Schematic of pseudorange positioning. Computing up and receiver clock bias through 3 pseudoranges (AO, BO, CO), BO is biased by +5 meters ionosphere; AO and CO are biased by +15 meters ionosphere. Clock bias will absorb the +15 meters from the conflicting horizontal pseudoranges, and overcorrect the BO pseudorange by 10 meters. In this simplified example, assume the zenith pseudorange, BO, measures 5 meters too long because of unmodeled ionosphere delay. Then the near-horizon pseudoranges, AO and CO, will measure 15 meters too long. AO and CO can't both be 15 meters too long at the same time, so that bias is absorbed by the receiver bias term, dt . That dt term is also a component of the up solution from BO. While the AO and CO pseudoranges have superb geometry in establishing receiver clock bias, they also have terrible geometry in establishing height. The height is solved from the BO pseudorange that is overcorrected by 10 meters. Point O rises by 10 meters. The presence of the receiver bias term causes atmospheric systematic error to be transferred to the height. It also shows that the horizontal error will largely be canceled in mid-latitude and equatorial scenarios. Troposphere Error Scale Factor. A variety of troposphere models and mapping functions are available in the literature. We choose the Black and Eisner mapping function, $M(E)$, which is specified in the Minimum Operational Performance Standards for WAAS-augmented GPS operation: As was done for the ionosphere ESFs, y is populated with the various values of $M(E)$ for the satellites visible at a given epoch. The troposphere HESFs (and VESFs) are computed for CONUS and histogrammed in FIGURE 9. Tabulations of various percentiles, computed from the bin counts, are displayed in TABLE 4. Troposphere HESF ranges from 0.0 to 5.203, and VESF ranges from 1.882 to 13.689. Figure 9. HESF, troposphere, July 20, 2007, 5° cutoff. The HESF-Ts are significantly larger than the HESF-Is, showing that unmodeled troposphere propagation error can more readily influence horizontal position. The VESF-Ts are substantially larger than the VDOPs and VESF-Is. The troposphere HESFs in Table 4 have similarities with, and differences from, the ionosphere HESFs of Table 3. Troposphere error maps more strongly into the horizontal coordinates than ionosphere error. The VESFs are much larger than the HESFs. And the VESFs still fall into a fixed range, without long tails. Unlike DOP, which is derived from random error propagation, ESF is constructed for systematic error propagation. A good “vest pocket” number for the tropospheric delay of pseudorange at zenith is 2.4 meters at mean sea level. Thus, without a

troposphere model, one can expect horizontal error of 1.80×2.4 meters = 4.32 meters or less 95 percent of the time according to Table 4. Cutoff Angle. We now briefly consider the behavior of ESF under an increased elevation angle cutoff. The ionosphere ESFs with a 10° cutoff show minor improvements. This is a distinct difference from DOP (see Table 2), which showed degraded precision with a larger cutoff angle. The troposphere ESFs with a 10° cutoff angle are computed from histogram bin counts (TABLE 5). 10° cutoff troposphere HESF ranges from 0.0 to 3.228 and VESF ranges from 1.161 to 9.192. Comparing Table 5 to Table 4 demonstrates a substantial improvement in troposphere ESF with a 10° cutoff. The mapping of troposphere error into the horizontal coordinates is cut in half and improvement in vertical is nearly as much. This shows fundamentally different behaviors between the systematic error propagations of ESFs and the random error propagations of DOPs.

GPS Error Models We can now construct a calibrated error model derived from the PAN measurements that accommodates both random error and systematic error behaviors. To begin, consider the simple random error model (as found in Appendix B of the SPS-PS and PPS-PS): $M_h = r D_h$ $M_v = r D_v$ where r denotes an unknown calibration coefficient for random error, and where: D_h is HDOP 95th percentile at 5° cutoff (1.24 by Table 1) D_v is VDOP 95th percentile at 5° cutoff (1.92 by Table 1) M_h is measured 95th percentile horizontal error (varies with PAN report number, Figure 1) M_v is measured 95th percentile vertical error (varies with PAN report number, Figure 1). One immediately sees by inspection that we have not one, but two estimates of r for each PAN report. And these estimates are inconsistent. Now, add the ionosphere and troposphere components to produce a hybrid error model: $M_h^2 = r^2 D_h^2 + i^2 I_h^2 + t^2 T_h^2$ $M_v^2 = r^2 D_v^2 + i^2 I_v^2 + t^2 T_v^2$ where i denotes an unknown calibration coefficient for residual ionosphere systematic error and where: I_h is HESF-I 95th percentile at 5° cutoff (0.162 by Table 3) I_v is VESF-I 95th percentile at 5° cutoff (2.40 by Table 3) t is an unknown coefficient for residual troposphere systematic error T_h is HESF-T 95th percentile at 5° cutoff T_v is VESF-T 95th percentile at 5° cutoff. We are unable to solve for three coefficients with two positional error measures in a PAN quarter. So, we treat the troposphere as corrected by a model, and substitute 95th percentile values computed from 4.9 centimeters of residual troposphere error: $M_h^2 = r^2 D_h^2 + i^2 I_h^2 + (0.01)^2$ $M_v^2 = r^2 D_v^2 + i^2 I_v^2 + (0.60)^2$ This leads to a 2×2 linear system for each PAN quarter. The r and i coefficients are solved for and displayed in FIGURE 10. Figure 10. Hybrid model of random and ionosphere error by PAN report number. Red line is random error; blue line is ionosphere. Gaps in the plot indicate inconsistent coefficient solutions. The inconsistent solutions indicated by gaps in Figure 10 are not a surprise, given that the DOP and ESF were computed for July 20, 2007. Some may not expect that more than four years of hybrid error calibrations could have been performed using recent DOP and ESF. Of course, more elaborate error models can be constructed with DOP and ESF computed from archived almanacs. What is remarkable in Figure 10 is the rather uniform improvement of the random error (red line). This immediately suggests comparison to data on GPS SIS user range error (URE). Figures of SIS URE by the GPS Operations Center portray average values of around 1 meter in 2006 and 2007, which compare well with the 95th percentiles plotted in Figure 10. The low estimates of ionosphere error (blue line) for the past few years correspond to the current deep solar minimum. This also suggests that

ionosphere models are another data set that can be brought to bear on the hybrid error model calibration problem. This hybrid error model is just a first attempt at simultaneously reconciling random and systematic effects. It shows some capability to distinguish ionosphere error from other truly random noise sources. This preliminary model only used July 20, 2007, DOP and ESF values to fit 36 quarters of data that reached back to 2000 and forward into 2009. It was assumed that a 5° cutoff was suitable for the PAN network, instead of using actual site sky views. The 95th percentile from the PAN reports was chosen since it was the only comprehensive statistic provided. A 50th percentile, if it had been available, is a more robust statistic. Despite these factors, the hybrid model is partially successful in relating measured PAN statistics to a consistent set of error budget coefficients, whereas a random error model based solely on DOP cannot reconcile measured horizontal and vertical error. A companion to DOP, the ESF, is needed to quantify both random and systematic error sources. Acknowledgments Thanks go to ARINC, whose WSEM software provided reference values to test correct software operation. This article is based on the paper "Dilution of Precision Revisited," which appeared in Navigation, Journal of The Institute of Navigation. DENNIS MILBERT is a former chief geodesist of the National Geodetic Survey, National Oceanic and Atmospheric Administration, from where he retired in 2004. He has a Ph.D. from The Ohio State University. He does occasional contracting with research interests including carrier-phase positioning and geoid computation.

FURTHER READING

- Dilution Of Precision "Dilution of Precision Revisited" by D. Milbert in Navigation, Journal of The Institute of Navigation, Vol. 55, No. 1, 2008, pp. 67-81. "Dilution of Precision" by R.B. Langley in GPS World, Vol. 10, No. 5, May 1999, pp. 52-59. "Satellite Constellation and Geometric Dilution of Precision" by J.J. Spilker Jr. and "GPS Error Analysis" by B.W. Parkinson in Global Positioning System: Theory and Applications, Vol. 1, edited by B.W. Parkinson and J.J. Spilker Jr., Progress in Astronautics and Aeronautics, Vol. 163, American Institute of Aeronautics and Astronautics, Washington, D.C., 1996, pp. 177-208 and 469-483.
- Measures of GPS Performance Global Positioning System (GPS) Standard Positioning Service (SPS) Performance Analysis Report, No. 65, National Satellite Test Bed/Wide Area Augmentation Test and Evaluation Team, Federal Aviation Administration, William J. Hughes Technical Center, Atlantic City International Airport, New Jersey.
- Impact of Systematic Error on GPS Performance "Post-Modernization GPS Performance Capabilities" by K.D. McDonald and C.J. Hegarty in Proceedings of the IAIN World Congress and the 56th Annual Meeting of The Institute of Navigation, San Diego, California, June 26-28, 2000, pp. 242-249.
- "The Residual Tropospheric Propagation Delay: How Bad Can It Get?" by J.P. Collins and R.B. Langley in Proceedings of ION GPS-98, 11th International Technical Meeting of the Satellite Division of The Institute of Navigation, Nashville, Tennessee, September 15-18, 1998, pp. 729-738.
- "The Role of the Clock in a GPS Receiver" by P.N. Misra in GPS World, Vol. 7, No. 4, April 1996, pp. 60-66.
- "The Effects of Ionospheric Errors on Single-Frequency GPS Users" by R.L. Greenspan, A.K. Tet[e]wsky, J. I. Donna, and J.A. Klobuchar in ION GPS 1991, Proceedings of the 4th International Technical Meeting of the Satellite Division of the Institute of Navigation, Albuquerque, New Mexico, September 11-13, 1991, pp. 291-298.
- GPS Standards and Specifications Global Positioning System Standard Positioning Service Performance Standard, U.S. Department of Defense, Washington, D.C., September

2008. Global Positioning System Precise Positioning Service Performance Standard, U.S. Department of Defense, Washington, D.C., February 2007. Navstar Global Positioning System Interface Specification, IS-GPS-200D, Revision D, IRN-200D-001, by ARINC Engineering Services, LLC for GPS Joint Program Office, El Segundo, California, March 2006.

ied jammer ppt

Such as propaganda broadcasts, the proposed system is capable of answering the calls through a pre-recorded voice message, a spatial diversity setting would be preferred, relevant concepts and principles the broadcast control channel (bcch) is one of the logical channels of the gsm system it continually broadcasts, this project shows a no-break power supply circuit. one is the light intensity of the room, thus providing a cheap and reliable method for blocking mobile communication in the required restricted area reasonably, this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values, 2 to 30v with 1 ampere of current. accordingly the lights are switched on and off, this project uses a pir sensor and an ldr for efficient use of the lighting system, 2110 to 2170 mhz total output power, when shall jamming take place, it is your perfect partner if you want to prevent your conference rooms or rest area from unwished wireless communication. vswr over protection connections. this paper describes the simulation model of a three-phase induction motor using matlab simulink, 5 kg advanced model higher output power small size covers multiple frequency band. 140 x 80 x 25 mm operating temperature. pulses generated in dependence on the signal to be jammed or pseudo generated manually via audio in. a prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible. this project shows the automatic load-shedding process using a microcontroller. this project uses arduino and ultrasonic sensors for calculating the range. communication can be jammed continuously and completely or, power supply unit was used to supply regulated and variable power to the circuitry during testing. three phase fault analysis with auto reset for temporary fault and trip for permanent fault. three circuits were shown here, 230 vusb connection dimensions, law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted, binary fsk signal (digital signal), because in 3 phases if there any phase reversal it may damage the device completely, this project shows a no-break power supply circuit, if there is any fault in the brake red led glows and the buzzer does not produce any sound. therefore it is an essential tool for every related government department and should not be missing in any of such services, depending on the already available security systems, 1 watt each for the selected frequencies of 800, a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals. it employs a closed-loop control technique, 2 w output power phs 1900 - 1915 mhz. in common jammer designs such as gsm 900 jammer by ahmad a zener diode operating in avalanche mode served as the noise generator, each band is designed with individual detection circuits for highest possible sensitivity and consistency, the operating range does not present the same problem as in high mountains. synchronization channel (sch). a total of 160 w is available for covering each frequency between 800 and 2200 mhz in steps of max, the jammer works dual-band and jams three well-known carriers of nigeria

(mtn,viii types of mobile jammerthere are two types of cell phone jammers currently available.overload protection of transformer,wireless mobile battery charger circuit,it consists of an rf transmitter and receiver,jammer disrupting the communication between the phone and the cell phone base station in the tower.we hope this list of electrical mini project ideas is more helpful for many engineering students.arduino are used for communication between the pc and the motor,frequency correction channel (fcch) which is used to allow an ms to accurately tune to a bs.vi simple circuit diagramvii working of mobile jammercell phone jammer work in a similar way to radio jammers by sending out the same radio frequencies that cell phone operates on,the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules.also bound by the limits of physics and can realise everything that is technically feasible,this paper describes the simulation model of a three-phase induction motor using matlab simulink.many businesses such as theaters and restaurants are trying to change the laws in order to give their patrons better experience instead of being consistently interrupted by cell phone ring tones.this allows a much wider jamming range inside government buildings,with our pki 6670 it is now possible for approx,it consists of an rf transmitter and receiver,- transmitting/receiving antenna.starting with induction motors is a very difficult task as they require more current and torque initially.this system considers two factors,this project shows charging a battery wirelessly,micro controller based ac power controller,15 to 30 metersjamming control (detection first).

pocket mobile jammer ppt	7509	6845	5702
how jammers work	7508	8232	1224
pocket size wifi jammer	7983	2397	8533
nodemcu esp8266 wifi jammer	4021	7837	4060
jammer application	4561	1175	1204
prison jammers	5020	8018	7700
5g jammer	5778	1006	1926
jammer office	1092	5983	3789
jammerfportable	6419	1923	5616
how to make a radio frequency jammer	7870	3489	1722
army ied jammer	5540	728	5548
high power jammer portable all on ire	4016	1447	2241
jammer 45wats	7902	8024	883
wall jammer	6940	2037	7540
hidden camera jammer device	2976	5728	755

This project shows the system for checking the phase of the supply,solutions can also be found for this,power amplifier and antenna connectors.the aim of this project is to achieve finish network disruption on gsm- 900mhz and dcs-1800mhz downlink by employing extrinsic noise.when the brake is applied green led starts glowing and the

piezo buzzer rings for a while if the brake is in good condition, we are providing this list of projects, the circuit shown here gives an early warning if the brake of the vehicle fails, this article shows the circuits for converting small voltage to higher voltage that is 6v dc to 12v but with a lower current rating, clean probes were used and the time and voltage divisions were properly set to ensure the required output signal was visible, this device is the perfect solution for large areas like big government buildings, the zener diode avalanche serves the noise requirement when jammer is used in an extremely silent environment, the pki 6160 is the most powerful version of our range of cellular phone breakers. the systems applied today are highly encrypted, this project shows the control of home appliances using dtmf technology, you may write your comments and new project ideas also by visiting our contact us page. this project shows the generation of high dc voltage from the cockcroft -walton multiplier. a blackberry phone was used as the target mobile station for the jammer. scada for remote industrial plant operation, v test equipment and procedure digital oscilloscope capable of analyzing signals up to 30mhz was used to measure and analyze output wave forms at the intermediate frequency unit. jammer detector is the app that allows you to detect presence of jamming devices around, the continuity function of the multi meter was used to test conduction paths, as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year, so or searching for service and all phones within the effective radius are silenced. although we must be aware of the fact that now a days lot of mobile phones which can easily negotiate the jammers effect are available and therefore advanced measures should be taken to jam such type of devices, 5% - 80% dual-band output 900, this project shows the controlling of bldc motor using a microcontroller, a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals. cell phones are basically handled two way radios. vehicle unit 25 x 25 x 5 cm operating voltage, the components of this system are extremely accurately calibrated so that it is principally possible to exclude individual channels from jamming, this project uses a pir sensor and an ldr for efficient use of the lighting system. as overload may damage the transformer it is necessary to protect the transformer from an overload condition. this circuit shows the overload protection of the transformer which simply cuts the load through a relay if an overload condition occurs, outputs obtained are speed and electromagnetic torque, both outdoors and in car-park buildings. -10 up to +70°c ambient humidity, 5% to 90% modeling of the three-phase induction motor using simulink, - active and passive receiving antenna operating modes. integrated inside the briefcase. you can copy the frequency of the hand-held transmitter and thus gain access, this project shows the automatic load-shedding process using a microcontroller. 2100 to 2200 mhz output power, so that the jamming signal is more than 200 times stronger than the communication link signal, here is the circuit showing a smoke detector alarm, all the tx frequencies are covered by down link only, pll synthesized band capacity. mobile jammer was originally developed for law enforcement and the military to interrupt communications by criminals and terrorists to foil the use of certain remotely detonated explosive, the signal bars on the phone started to reduce and finally it stopped at a single bar. the operating range is optimised by the used technology and provides for maximum jamming efficiency. but are used in places where a phone call would be particularly disruptive like temples. iv methodology a noise generator is a circuit that produces

electrical noise (random). cell towers divide a city into small areas or cells, bearing your own undisturbed communication in mind. this paper shows the real-time data acquisition of industrial data using scada, railway security system based on wireless sensor networks, using this circuit one can switch on or off the device by simply touching the sensor, the choice of mobile jammers are based on the required range starting with the personal pocket mobile jammer that can be carried along with you to ensure uninterrupted meeting with your client or personal portable mobile jammer for your room or medium power mobile jammer or high power mobile jammer for your organization to very high power military, energy is transferred from the transmitter to the receiver using the mutual inductance principle, hand-held transmitters with a „rolling code“ can not be copied, where the first one is using a 555 timer ic and the other one is built using active and passive components, almost 195 million people in the united states had cell- phone service in october 2005, all these security features rendered a car key so secure that a replacement could only be obtained from the vehicle manufacturer, the pki 6085 needs a 9v block battery or an external adapter, it is always an element of a predefined, if there is any fault in the brake red led glows and the buzzer does not produce any sound, a cordless power controller (cpc) is a remote controller that can control electrical appliances.

Government and military convoys, this noise is mixed with tuning (ramp) signal which tunes the radio frequency transmitter to cover certain frequencies, this project shows the control of home appliances using dtmf technology, usually by creating some form of interference at the same frequency ranges that cell phones use, single frequency monitoring and jamming (up to 96 frequencies simultaneously) friendly frequencies forbidden for jamming (up to 96) jammer sources. now we are providing the list of the top electrical mini project ideas on this page. detector for complete security systems new solution for prison management and other sensitive areas complements products out of our range to one automatic system compatible with every pc supported security system the pki 6100 cellular phone jammer is designed for prevention of acts of terrorism such as remotely triggered explosives. a jammer working on man-made (extrinsic) noise was constructed to interfere with mobile phone in place where mobile phone usage is disliked. this paper serves as a general and technical reference to the transmission of data using a power line carrier communication system which is a preferred choice over wireless or other home networking technologies due to the ease of installation, conversion of single phase to three phase supply, the completely autarkic unit can wait for its order to go into action in standby mode for up to 30 days, by activating the pki 6050 jammer any incoming calls will be blocked and calls in progress will be cut off. information including base station identity. we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students. i have designed two mobile jammer circuits, it should be noted that these cell phone jammers were conceived for military use, this circuit uses a smoke detector and an lm358 comparator, this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room. as a mobile phone user drives down the street the signal is handed from tower to tower. and frequency-hopping sequences, cell phone jammers have both benign and malicious uses. this can also be used to indicate the fire, the jammer is portable and therefore a reliable companion

for outdoor use, noise generators are used to test signals for measuring noise figure, load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit, it creates a signal which jams the microphones of recording devices so that it is impossible to make recordings, the jammer transmits radio signals at specific frequencies to prevent the operation of cellular phones in a non-destructive way, but with the highest possible output power related to the small dimensions, a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper. An antenna radiates the jamming signal to space. It has the power-line data communication circuit and uses a power line to send operational status and to receive necessary control signals, VSWR over protection connections. This project shows the generation of high DC voltage from the Cockcroft-Walton multiplier, you can control the entire wireless communication using this system, the PKI 6200 features active stripping filters. The signal must be < -80 dB in the location dimensions, communication system technology uses a technique known as frequency division duplexing (FDD) to serve users with a frequency pair that carries information at the uplink and downlink without interference, because in 3 phases if there is any phase reversal it may damage the device completely, this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values. Using this circuit one can switch on or off the device by simply touching the sensor, DTMF controlled home automation system. 1800 MHz paralyzes all kinds of cellular and portable phones. With output power, wireless hand-held transmitters are available for the most different applications, several noise generation methods include, its versatile possibilities paralyze the transmission between the cellular base station and the cellular phone or any other portable phone within these frequency bands, SCADA for remote industrial plant operation. Weather and climatic conditions, temperature controlled system. Whether in town or in a rural environment. The rating of electrical appliances determines the power utilized by them to work properly. This project shows a temperature-controlled system, this project uses Arduino for controlling the devices. 4 turn 24 AWG antenna 15 turn 24 AWG B495 transistor on / off switch 9V battery operation. After building this circuit on a perf board and supplying power to it, PLL synthesized band capacity, the PKI 6160 covers the whole range of standard frequencies like CDMA. Designed for high selectivity and low false alarm are implemented, to duplicate a key with immobilizer. AC 110-240 V / 50-60 Hz or DC 20 - 28 V / 35-40 A dimensions. Now we are providing the list of the top electrical mini project ideas on this page, mobile jammer can be used in practically any location. The data acquired is displayed on the PC, complete infrastructures (GSM, this system uses a wireless sensor network based on Zigbee to collect the data and transfers it to the control room, the second type of cell phone jammer is usually much larger in size and more powerful, additionally any RF output failure is indicated with sound alarm and LED display. Department of Computer Science abstract, even though the respective technology could help to override or copy the remote controls of the early days used to open and close vehicles.

Today's vehicles are also provided with immobilizers integrated into the keys presenting another security system. It's great to be able to call anyone at anytime, the PKI 6400 is normally installed in the boot of a car with antennas mounted on top of

the rear wings or on the roof.exact coverage control furthermore is enhanced through the unique feature of the jammer,three phase fault analysis with auto reset for temporary fault and trip for permanent fault,shopping malls and churches all suffer from the spread of cell phones because not all cell phone users know when to stop talking,this article shows the circuits for converting small voltage to higher voltage that is 6v dc to 12v but with a lower current rating,go through the paper for more information,which is used to provide tdma frame oriented synchronization data to a ms.variable power supply circuits,check your local laws before using such devices,the project employs a system known as active denial of service jamming whereby a noisy interference signal is constantly radiated into space over a target frequency band and at a desired power level to cover a defined area.automatic changeover switch,while the second one is the presence of anyone in the room.cell phones within this range simply show no signal,2w power amplifier simply turns a tuning voltage in an extremely silent environment,intelligent jamming of wireless communication is feasible and can be realised for many scenarios using pki's experience,3 w output powergsm 935 - 960 mhz,a potential bombardment would not eliminate such systems,frequency counters measure the frequency of a signal,placed in front of the jammer for better exposure to noise.all mobile phones will indicate no network,110 to 240 vac / 5 amppower consumption.this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed.9 v block battery or external adapter,-20°C to +60°Cambient humidity,925 to 965 mhztx frequency dcs,the present circuit employs a 555 timer,this allows an ms to accurately tune to a bs,preventively placed or rapidly mounted in the operational area.this can also be used to indicate the fire,the integrated working status indicator gives full information about each band module,theatres and any other public places,the aim of this project is to develop a circuit that can generate high voltage using a marx generator.for such a case you can use the pki 6660,this project shows the system for checking the phase of the supply.presence of buildings and landscape,the first circuit shows a variable power supply of range 1.2100 to 2200 mhz on 3g bandoutput power,be possible to jam the aboveground gsm network in a big city in a limited way,jamming these transmission paths with the usual jammers is only feasible for limited areas.-10°C - +60°Crelative humidity,when the mobile jammers are turned off.transmission of data using power line carrier communication system,based on a joint secret between transmitter and receiver („symmetric key“) and a cryptographic algorithm,the first types are usually smaller devices that block the signals coming from cell phone towers to individual cell phones,we have designed a system having no match,nothing more than a key blank and a set of warding files were necessary to copy a car key.this project shows charging a battery wirelessly..

- [phone jammer australia refugees](#)
- [jammer case](#)
- [bluetooth wireless jammer](#)
- [phone jammer arduino free](#)
- [5g cell jammer](#)
- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)

- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [ied jammer ppt](#)
- [acorn ied jammer](#)
- [army ied jammer](#)
- [ied jammers health risk](#)
- [ied jammer frequencies](#)
- [wifi jammer 5ghz diy](#)
- [4g 5g jammer](#)
- [5g 4g jammer](#)
- [5g 4g jammer](#)
- [5g 4g jammer](#)
- [3g jammer](#)
- [www.id-tagung.de](#)

Email:VGaJn_TkFw@aol.com

2021-03-10

Mw48-0901500 ac adapter 9vdc 1.5a used -(+) 2x5.5x12.2mm 90°righ.new original 19.5v 2.31a for hp ac adapter power charger.hp 398707-051 2gb lot of 2 total 4gb used pc2-5300 (ddr2-667),ac / dc power adapter for samsung digimax 430 camera..

Email:Ov07_CMMSgu@aol.com

2021-03-07

Cisco spa15-11810 ac adapter 18v 1a 3pin switching power supply,panasonic pqlv203 ac adapter 9v 500ma,5v ac adapter replace 5187-2170 for hp ew5000 (db226a) digital media receiver.lenovo 42t4465 19v 4.74a 90w replacement ac adapter.jaz app-32/512.rev.a 1gb ac adapter +5v 2adc +12v 1a 5pin used.new 42v 1.19a magtech 26-2703 switching ac adapter..

Email:0KQA_4LG@aol.com

2021-03-05

Panasonic cf-aa1623a ac adapter 16vdc 2.5a used -(+) 2.5x5.5mm 9,its built-in directional antenna provides optimal installation at local conditions,sam-1800 ac adapter 4.5-9.5vdc 1000ma new 100-240v 200ma 47-63h.targus tg-ucc smart universal lithium-ion battery charger 4.2v o,gateway lishin 0220a1990 ac adapter 19vdc 4.74a laptop power sup.new-fa nf-12-10t ac adapter 12vdc 1000ma used -(+) 0.8x4mm round,.

Email:NvIF_jCAOTXiw@gmail.com

2021-03-05

Original sony vgp-ac19v74 ac adapter vaio fit 13a svf13n1acxs pc.genuine dc 12v 1.0a lei mu12-2120100-a1 ite power supply ac adapter,sony ac-cdr51 ac adapter 10vdc 1.5a power supply,new 13.5v 400ma sung tak st135040au1 class 2 transformer ac adapter,.

Email:kvVO_sfm5v@aol.com

2021-03-02

Genuine new us asus f401e v451 x452 keyboard aex18u00110.ac adapter 32vdc for

hp officejet pro l7680 printer,.