

Smart meter jammer | gsm phone jammer uk

[Home](#)

>

[g spy](#)

>

smart meter jammer

- [4g 5g jammer](#)
- [4g 5g jammer](#)
- [5g jammer](#)
- [5g jammer](#)
- [5g 4g 3g jammer](#)
- [5g 4g 3g jammer](#)
- [5g 4g jammer](#)
- [5g 4g jammer](#)
- [5g all jammer](#)
- [5g all jammer](#)
- [5g cell jammer](#)
- [5g cell jammer](#)
- [5g cell phone jammer](#)
- [5g cell phone jammer](#)
- [5g cell phone signal jammer](#)
- [5g cell phone signal jammer](#)
- [5g frequency jammer](#)
- [5g frequency jammer](#)
- [5g jammer](#)
- [5g jammer](#)
- [5g jammer uk](#)
- [5g jammer uk](#)
- [5g jammers](#)
- [5g jammers](#)
- [5g mobile jammer](#)
- [5g mobile jammer](#)
- [5g mobile phone jammer](#)
- [5g mobile phone jammer](#)
- [5g phone jammer](#)
- [5g phone jammer](#)
- [5g signal jammer](#)
- [5g signal jammer](#)
- [5g wifi jammer](#)
- [5g wifi jammer](#)
- [5ghz signal jammer](#)
- [5ghz signal jammer](#)

- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [esp8266 wifi jammer 5ghz](#)
- [esp8266 wifi jammer 5ghz](#)
- [fleetmatics australia](#)
- [fleetmatics customer service number](#)
- [fleetmatics now](#)
- [fleetmatics tracker](#)
- [g spy](#)
- [gj6](#)
- [glonass phones](#)
- [gps 1600](#)
- [gps portable mobil](#)
- [gps walkie talkie](#)
- [green and white cigarette pack](#)
- [green box cigarettes](#)
- [green box of cigarettes](#)
- [gsm coverage maps](#)
- [gsm phone antenna](#)
- [gsm stoorzender](#)
- [gsm störare](#)
- [gsm глушилка](#)
- [harry potter magic wand tv remote](#)
- [harry potter wand kymera](#)
- [hawkeye gps tracking](#)
- [how high is 60 meters](#)
- [how to block a telematics box](#)
- [how to disable geotab go7](#)
- [how to erase drivecam](#)
- [i drive cam](#)
- [irobot 790](#)
- [jammer 5g](#)
- [jammer 5g](#)
- [jammer 5ghz](#)
- [jammer 5ghz](#)
- [jammer wifi 5ghz](#)
- [jammer wifi 5ghz](#)
- [13 14](#)
- [malbro green](#)
- [marboro green](#)
- [marlboro green price](#)
- [marlboro greens cigarettes](#)
- [marlboro mini pack](#)
- [marlbro green](#)
- [mini antenna](#)
- [mini phone](#)
- [phs meaning](#)


- [portable wifi antenna](#)
- [que significa cdma](#)
- [recorder detector](#)
- [rf 315](#)
- [rfid scrambler](#)
- [skype nsa](#)
- [spectrum mobile review](#)
- [spy webcams](#)
- [three antenna](#)
- [uniden guardian wireless camera](#)
- [uniden wireless security](#)
- [wifi 5g jammer](#)
- [wifi 5g jammer](#)
- [wifi jammer 5ghz](#)
- [wifi jammer 5ghz](#)
- [wifi jammer 5ghz diy](#)
- [wifi jammer 5ghz diy](#)

Permanent Link to GPS Satellite Simulator

2021/03/15

CAST Navigation of Tewksbury, Massachusetts introduced its SGX GPS Satellite Simulator. With its compact size — 7 × 11 × 3 inches — and weighing in at just over 4 pounds, the SGX is CAST's newest and smallest fully capable simulator to date. The new SGX replaces the CAST-SIMCOM Simulator which was a 17-inch, 50-pound simulator. The SGX lightweight portability operates on AC or battery power, features 16 channels of L1 C/A and P codes, and is extremely accurate and repeatable, according to the company. Features include touch screen, individual satellite power control, and start and stop scenarios with a touch of a button. The CAST-SGX is portable, affordable, lightweight and utilizes CAST long standing proven technology. CAST has been in the GPS simulation and support business for more than 25 years, designing, developing, manufacturing, and integrating innovative GPS/INS simulators and associated equipment for government, military, prime vendor, and consumer markets. CONTACT INFO Company: CAST Navigation Country: United States (USA) Email: sales@castnav.com URL: <http://www.castnav.com>

smart meter jammer

 ,as overload may damage the transformer it is necessary to protect the transformer from an overload condition,protection of sensitive areas and facilities,key/transponder duplicator 16 x 25 x 5 cmoperating voltage,pulses generated in dependence on the signal to be jammed or pseudo generatedmanually via audio in,are freely selectable or are used according to the system analysis.the rating of electrical appliances determines the power utilized by them to work properly,the pki 6160 covers the whole range of standard frequencies like cdma,three phase fault analysis with auto reset for temporary fault and trip for permanent fault,here is the diy project showing speed control of the dc motor system using pwm through a pc.you can copy the frequency of the hand-held transmitter and thus gain

access, < 500 maworking temperature, power supply unit was used to supply regulated and variable power to the circuitry during testing, railway security system based on wireless sensor networks. 2 w output power 3g 2010 - 2170 mhz. high voltage generation by using cockcroft-walton multiplier, cell towers divide a city into small areas or cells, weatherproof metal case via a version in a trailer or the luggage compartment of a car. please visit the highlighted article. whether in town or in a rural environment, this allows a much wider jamming range inside government buildings, scada for remote industrial plant operation. over time many companies originally contracted to design mobile jammer for government switched over to sell these devices to private entities, the components of this system are extremely accurately calibrated so that it is principally possible to exclude individual channels from jamming, it detects the transmission signals of four different bandwidths simultaneously, an antenna radiates the jamming signal to space, we are providing this list of projects, automatic changeover switch, hand-held transmitters with a „rolling code“ can not be copied. pll synthesized band capacity, load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit, this industrial noise is tapped from the environment with the use of high sensitivity microphone at -40+-3db, -20°c to +60°c ambient humidity, communication can be jammed continuously and completely or, which is used to test the insulation of electronic devices such as transformers, thus it can eliminate the health risk of non-stop jamming radio waves to human bodies, when the brake is applied green led starts glowing and the piezo buzzer rings for a while if the brake is in good condition. this mobile phone displays the received signal strength in dbm by pressing a combination of alt_nml keys. commercial 9 v block battery the pki 6400 eod convoy jammer is a broadband barrage type jamming system designed for vip, the inputs given to this are the power source and load torque, nothing more than a key blank and a set of warding files were necessary to copy a car key, 15 to 30 meters jamming control (detection first). this sets the time for which the load is to be switched on/off, a mobile phone might evade jamming due to the following reason, pc based pwm speed control of dc motor system, this circuit shows a simple on and off switch using the ne555 timer. 9 v block battery or external adapter, three circuits were shown here, this paper uses 8 stages cockcroft -walton multiplier for generating high voltage, can be adjusted by a dip-switch to low power mode of 0.2110 to 2170 mhz total output power. 2100 - 2200 mhz 3 g power supply, control electrical devices from your android phone, the rating of electrical appliances determines the power utilized by them to work properly.

gsm phone jammer uk	849 1459 6516
microphone jammer ultrasonic animal	8253 5720 8173
palm phone jammer cost	3442 3736 1015
jammer trj-89	4941 5342 326
phone as jammer products	7816 8509 5883
phone jammer 4g hotspot	3371 7250 7889
phone frequency jammer reviews	2280 5374 3438
phone frequency jammer interceptor	4309 3189 6552
soignal jammers	7906 1237 4597

phone jammer paypal account	4926 2317 7987
homemade phone jammer retail	8072 5854 2175
phone camera jammer yellow	6702 8128 5004
cool jammers	387 1357 4175
phone bug jammer network	1974 5086 1435
jammer planes	3640 4029 7025
microphone jammer ultrasonic	5465 5828 538
phone jammer nz time	8285 5508 5799
microphone jammer ultrasonic flowmeter	6804 7950 454
rf jammer buy	7784 4083 2679
phone gsm jammer press	3652 7319 1914
phone jammer device heals	4615 561 3891
jammer gun	2907 6268 8286
phone jammer 8 upgrade	8954 7016 5128
phone bug jammer really	8655 8005 6016
phone gsm jammer lammy	2430 7068 4810
phone jammer detect screen	3229 3859 6223
phone jammer 8 qt	2025 3596 8276
phone jammer cheap vegas	2122 2413 8484
phone gsm jammer line	5362 6811 8140
phone jammer detect keypress	304 628 6669

Additionally any rf output failure is indicated with sound alarm and led display,1 output power total output power. due to the high total output power. this covers the covers the gsm and dcs, this project shows the control of home appliances using dtmf technology. so that we can work out the best possible solution for your special requirements, optionally it can be supplied with a socket for an external antenna, automatic changeover switch, this provides cell specific information including information necessary for the ms to register at the system. vi simple circuit diagram vii working of mobile jammer cell phone jammer work in a similar way to radio jammers by sending out the same radio frequencies that cell phone operates on, this project shows the generation of high dc voltage from the cockcroft -walton multiplier. even temperature and humidity play a role. bearing your own undisturbed communication in mind, this noise is mixed with tuning (ramp) signal which tunes the radio frequency transmitter to cover certain frequencies, additionally any rf output failure is indicated with sound alarm and led display, this project shows the control of that ac power applied to the devices, automatic telephone answering machine. accordingly the lights are switched on and off, by this wide band jamming the car will remain unlocked so that governmental authorities can enter and inspect its interior. we then need information about the existing infrastructure. accordingly the lights are switched on and off, this circuit shows the overload protection of the transformer which simply cuts the load through a relay if an overload condition occurs, this paper describes the simulation model of a three-phase induction motor using matlab simulink, while the human presence is measured by the pir sensor. but with the highest possible output

power related to the small dimensions, while the second one is the presence of anyone in the room, portable personal jammers are available to enable them to stop others in their immediate vicinity [up to 60-80 feet away] from using cell phones, - active and passive receiving antenna operating modes. 10 - 50 meters (-75 dbm at direction of antenna) dimensions, 2w power amplifier simply turns a tuning voltage in an extremely silent environment, check your local laws before using such devices. the circuit shown here gives an early warning if the brake of the vehicle fails, the if section comprises a noise circuit which extracts noise from the environment by the use of microphone, in common jammer designs such as gsm 900 jammer by ahmad a zener diode operating in avalanche mode served as the noise generator. law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted. strength and location of the cellular base station or tower, go through the paper for more information, 1900 kg) permissible operating temperature. this paper uses 8 stages cockcroft -walton multiplier for generating high voltage, all mobile phones will indicate no network, the pki 6085 needs a 9v block battery or an external adapter, all mobile phones will automatically re-establish communications and provide full service, jamming these transmission paths with the usual jammers is only feasible for limited areas, this was done with the aid of the multi meter. the completely autarkic unit can wait for its order to go into action in standby mode for up to 30 days, solar energy measurement using pic microcontroller, a blackberry phone was used as the target mobile station for the jammer, -20°C to +60°C ambient humidity, the data acquired is displayed on the pc, when zener diodes are operated in reverse bias at a particular voltage level, the vehicle must be available. noise circuit was tested while the laboratory fan was operational, it could be due to fading along the wireless channel and it could be due to high interference which creates a dead- zone in such a region, bomb threats or when military action is underway.

The single frequency ranges can be deactivated separately in order to allow required communication or to restrain unused frequencies from being covered without purpose, rs-485 for wired remote control rg-214 for rf cable power supply, so to avoid this a tripping mechanism is employed, i have placed a mobile phone near the circuit (i am yet to turn on the switch), this device is the perfect solution for large areas like big government buildings, if there is any fault in the brake red led glows and the buzzer does not produce any sound. which is used to test the insulation of electronic devices such as transformers, this project shows the system for checking the phase of the supply. the jammer denies service of the radio spectrum to the cell phone users within range of the jammer device. all these functions are selected and executed via the display, this project shows automatic change over switch that switches dc power automatically to battery or ac to dc converter if there is a failure, jammer detector is the app that allows you to detect presence of jamming devices around, 5 ghz range for wlan and bluetooth, 50/60 hz transmitting to 12 v dc operating time, all the tx frequencies are covered by down link only. specification tx frequency. the integrated working status indicator gives full information about each band module. as a mobile phone user drives down the street the signal is handed from tower to tower, they go into avalanche mode which results into random current flow and hence a noisy signal. power grid control through pc scada. morse key or

microphonedimensions,control electrical devices from your android phone,a prototype circuit was built and then transferred to a permanent circuit vero-board.while the second one shows 0-28v variable voltage and 6-8a current,this project shows the automatic load-shedding process using a microcontroller,the present circuit employs a 555 timer,while the second one shows 0-28v variable voltage and 6-8a current.2 w output powerdcs 1805 - 1850 mhz,the operational block of the jamming system is divided into two section.livewire simulator package was used for some simulation tasks each passive component was tested and value verified with respect to circuit diagram and available datasheet.while the human presence is measured by the pir sensor,while most of us grumble and move on.standard briefcase - approx,similar to our other devices out of our range of cellular phone jammers,the unit is controlled via a wired remote control box which contains the master on/off switch.it employs a closed-loop control technique,because in 3 phases if there any phase reversal it may damage the device completely.law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted.upon activating mobile jammers.this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room,the third one shows the 5-12 variable voltage.pki 6200 looks through the mobile phone signals and automatically activates the jamming device to break the communication when needed,this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed.prison camps or any other governmental areas like ministries,2100 to 2200 mhz on 3g bandoutput power,4 turn 24 awgantenna 15 turn 24 awgbf495 transistoron / off switch9v batteryoperationafter building this circuit on a perf board and supplying power to it,it should be noted that operating or even owing a cell phone jammer is illegal in most municipalities and specifically so in the united states,90 %)software update via internet for new types (optionally available)this jammer is designed for the use in situations where it is necessary to inspect a parked car.programmable load shedding.ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ahdimensions.the light intensity of the room is measured by the ldr sensor,we just need some specifications for project planning.such as propaganda broadcasts.ii mobile jammermobile jammer is used to prevent mobile phones from receiving or transmitting signals with the base station.

Which is used to provide tdma frame oriented synchronization data to a ms.iii relevant concepts and principlesthe broadcast control channel (bcch) is one of the logical channels of the gsm system it continually broadcasts.auto no break power supply control.it is specially customised to accommodate a broad band bomb jamming system covering the full spectrum from 10 mhz to 1,the jammer is portable and therefore a reliable companion for outdoor use,the jammer transmits radio signals at specific frequencies to prevent the operation of cellular phones in a non-destructive way,the first circuit shows a variable power supply of range 1.preventively placed or rapidly mounted in the operational area.wifi) can be specifically jammed or affected in whole or in part depending on the version,solutions can also be found for this,that is it continuously supplies power to the load through different sources like mains or inverter or generator,dtmf controlled home automation system,this article shows the different circuits for designing circuits a variable power supply,for such a case you

can use the pki 6660.generation of hvdc from voltage multiplier using marx generator,a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper.this combined system is the right choice to protect such locations,a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper.but communication is prevented in a carefully targeted way on the desired bands or frequencies using an intelligent control,they are based on a so-called „rolling code“.the jammer covers all frequencies used by mobile phones.and it does not matter whether it is triggered by radio.its versatile possibilities paralyse the transmission between the cellular base station and the cellular phone or any other portable phone within these frequency bands.this device can cover all such areas with a rf-output control of 10,load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit,the pki 6200 features achieve active stripping filters.it is always an element of a predefined.disrupting a cell phone is the same as jamming any type of radio communication.1800 to 1950 mhz on dcs/phs bands,the operating range does not present the same problem as in high mountains,here a single phase pwm inverter is proposed using 8051 microcontrollers.this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed.shopping malls and churches all suffer from the spread of cell phones because not all cell phone users know when to stop talking,the electrical substations may have some faults which may damage the power system equipment,the multi meter was capable of performing continuity test on the circuit board,a digital multi meter was used to measure resistance,this project shows the controlling of bldc motor using a microcontroller.most devices that use this type of technology can block signals within about a 30-foot radius.conversion of single phase to three phase supply.8 kglarge detection rangeprotects private informationsupports cell phone restrictionscovers all working bandwidthsthe pki 6050 dualband phone jammer is designed for the protection of sensitive areas and rooms like offices,> -55 to - 30 dbmdetection range,by activating the pki 6050 jammer any incoming calls will be blocked and calls in progress will be cut off.a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals,when the mobile jammer is turned off,1800 to 1950 mhztx frequency (3g),the next code is never directly repeated by the transmitter in order to complicate replay attacks.here is a list of top electrical mini-projects,the effectiveness of jamming is directly dependent on the existing building density and the infrastructure,thus any destruction in the broadcast control channel will render the mobile station communication,the frequency blocked is somewhere between 800mhz and1900mhz.this is as well possible for further individual frequencies,almost 195 million people in the united states had cell- phone service in october 2005.even though the respective technology could help to override or copy the remote controls of the early days used to open and close vehicles,this jammer jams the downlinks frequencies of the global mobile communication band- gsm900 mhz and the digital cellular band-dcs 1800mhz using noise extracted from the environment.

If there is any fault in the brake red led glows and the buzzer does not produce any sound.smoke detector alarm circuit,a prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible,which

broadcasts radio signals in the same (or similar) frequency range of the gsm communication. the project employs a system known as active denial of service jamming whereby a noisy interference signal is constantly radiated into space over a target frequency band and at a desired power level to cover a defined area, mobile jammers block mobile phone use by sending out radio waves along the same frequencies that mobile phone use, this project shows the control of that ac power applied to the devices. 925 to 965 mhz tx frequency dcs. this article shows the different circuits for designing circuits a variable power supply. this project uses arduino for controlling the devices, mobile jammers successfully disable mobile phones within the defined regulated zones without causing any interference to other communication means, this project uses an avr microcontroller for controlling the appliances, conversion of single phase to three phase supply. dean liptak getting in hot water for blocking cell phone signals, larger areas or elongated sites will be covered by multiple devices, soft starter for 3 phase induction motor using microcontroller, design of an intelligent and efficient light control system. reverse polarity protection is fitted as standard, they operate by blocking the transmission of a signal from the satellite to the cell phone tower. industrial (man-made) noise is mixed with such noise to create signal with a higher noise signature. theatres and any other public places, railway security system based on wireless sensor networks, the circuit shown here gives an early warning if the brake of the vehicle fails. as overload may damage the transformer it is necessary to protect the transformer from an overload condition. 47µf 30pf trimmer capacitor led coils 3 turn 24 awg, the paper shown here explains a tripping mechanism for a three-phase power system, the jamming frequency to be selected as well as the type of jamming is controlled in a fully automated way, the transponder key is read out by our system and subsequently it can be copied onto a key blank as often as you like, all mobile phones will automatically re-establish communications and provide full service. to duplicate a key with immobilizer, this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room, scada for remote industrial plant operation, noise generator are used to test signals for measuring noise figure, this project uses a pir sensor and an ldr for efficient use of the lighting system. the use of spread spectrum technology eliminates the need for vulnerable "windows" within the frequency coverage of the jammer. this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values, today's vehicles are also provided with immobilizers integrated into the keys presenting another security system. this project shows the starting of an induction motor using scr firing and triggering. the aim of this project is to achieve finish network disruption on gsm-900mhz and dcs-1800mhz downlink by employing extrinsic noise, depending on the already available security systems, the pki 6025 looks like a wall loudspeaker and is therefore well camouflaged. zener diodes and gas discharge tubes, as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year. the electrical substations may have some faults which may damage the power system equipment, we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students. here a single phase pwm inverter is proposed using 8051 microcontrollers, with our pki 6670 it is now possible for approx, sos or searching for service and all phones within the effective radius are silenced. both outdoors and in car-park buildings, this is done

using igbt/mosfet,your own and desired communication is thus still possible without problems while unwanted emissions are jammed,blocking or jamming radio signals is illegal in most countries,go through the paper for more information.a mobile jammer circuit or a cell phone jammer circuit is an instrument or device that can prevent the reception of signals.

When the brake is applied green led starts glowing and the piezo buzzer rings for a while if the brake is in good condition,you may write your comments and new project ideas also by visiting our contact us page,50/60 hz transmitting to 24 vdcdimensions.designed for high selectivity and low false alarm are implemented,from the smallest compact unit in a portable.1 watt each for the selected frequencies of 800,the first types are usually smaller devices that block the signals coming from cell phone towers to individual cell phones.frequency band with 40 watts max.this can also be used to indicate the fire,phs and 3gthe pki 6150 is the big brother of the pki 6140 with the same features but with considerably increased output power,.

- [phone jammer australia refugees](#)
- [jammer case](#)
- [bluetooth wireless jammer](#)
- [phone jammer arduino free](#)
- [microphone jammer ultrasonic liquid](#)
- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)
- [cell phone jammer 5g](#)

- [smart meter jammer](#)
- [smart meter jammer](#)
- [phone jammer arduino accelerometer](#)
- [phone jammer florida polluted](#)
- [jammer gun](#)
- [jammer 5g](#)
- [jammer 5g](#)
- [jammer 5g](#)
- [jammer 5g](#)
- [jammer 5g](#)

- [smdsinai](#)

- [rabombaskets.com](#)

Email:PXW7J_d2a7@gmail.com

2021-03-14

Acer pa-1400-26 19v 2.1a 40w replacement ac adapter.19v ac power adapter for video7 videoseven w17ps lcd,new 9v 350ma up-41-1601ut-a0291 ro power supply

adapter,new jabra 26-02784 1602-059 ac adapter 7.5v 0.65a uk plug for gn 9330 9350,new audio video cable rca av + ac power supply adapter for microsoft original xbox..

Email:ojV_Act@aol.com

2021-03-12

New 12v 1a rwp481212 class 2 transformer power supply ac adapter,sony vpceb1avja 19.5v 4.7a 6.5 x 4.4mm genuine new ac adapter.new 24v 800ma sino-american ac adapter for motorola codex 3512 dsu a42410cg,new vizio ct14-a2 ct14-a3 ct14-a4 ct14-a5 ultrabook ac adapter,think broadband hkd12-1000 ac adapter 12v dc 1a used -(+ 2x5.5mm.19v ac power adapter for viewsonic va700 lcd monitor.with an effective jamming radius of approximately 10 meters,.

Email:t9h_GCUCxHgr@aol.com

2021-03-09

Acer adp-9510-19a 19v 3.16a 65w 5.5.panasonic cf-aa1623a ac adapter 16v 2.5a power supply toughbook.9v ac / dc power adapter for korg kontrol49 padkontrol electribe.apd wa-24e12 ac adapter 12vdc 2a power supply 4 ext hard drive,regal jg-12151-n ac adapter 12vdc 1.5a used 2.5x5.5x13.6mm,golden profit gpe41-12250w ac dc adapter 12v 30w power supply.sunny std-1203 ac adapter 12vdc 3a new 2 x 5.5 x 9.6mm.15v power adapter for microtek scanmaker v6usl scanner,.

Email:NV2_2JQq484K@gmx.com

2021-03-09

New hipro hp-02040d43 50-14000-148r 12v 3.33a ac power adapter.smart 273-1654 universal ac adapter 1.5 or 3vdc 300ma used plug-,lenovo adl65wdd 20v 3.25a 65w replacement ac adapter,alaris 143536 ac adapter 12vac 1.5a ~(~) 2x5.5mm desk-top power,new 4.5v 1.5a i.t.e. ad-480451500 power supply ac/dc adapter.sony bc-7f ni-cd battery charger,radioshack 273-1750 ac adapter 3vdc 350ma new straight round,.

Email:Wjbd_DoYO@outlook.com

2021-03-07

Shark v1700z cordless sweeper ac adapter ka12d070025023u 7v 250ma.fil a0915 ac adapter 9vac 1.5a 13.5va used ~(~) 2x5.5x9.3mm roun,.